

Product data sheet

SCHUKO® socket with surge voltage protection



Reference number

A 521 KIUF

SCHUKO® socket 16 A / 250 V ~

with surge voltage protection
with child protection (shutter)
 Screw terminals for wires up to 2.5 mm²

Without claws: ref.-no. with additional "N", e.g.: ..521 N..

Intended use

- Type 3 fine protection for protecting electrical and electronic devices against transient power surges according to EN 61643-11
- For use only in combination with Type 1 coarse protection and Type 2 medium protection
- For use in TN, TT and IT systems
- Stationary installation indoors
- Installation in flush box according to DIN 49073

Product characteristics

- The device protects electrical and electronic devices against transient power surges.
- Failure of the protection function is indicated by an acoustic and visual signal.

Aufdruck "Nur für EDV", "ZSV", "SV" gegen Aufpreis (Art.-Nr.: ..1520.. EDV, ..1520.. ZSV, ..1520.. SV).

Technical data

Surge voltage protection:	type 3 surge arrester
Rated voltage UN:	AC 230 V ~
Mains frequency:	50/60 Hz
Max. continuous voltage UC:	AC 255 V ~
Open-circuit voltage UOC:	4 kV
Protection level between L/N:	≤ 1.25 kV
Protection level between L/PE:	≤ 1.25 kV
Protection level between N/PE:	≤ 1.25 kV
Rated load current IL:	16 A
Ambient temperature:	-5 ... +40 °C

Duroplastic (scratch-proof) glossy

Colour:
ivory

Material:
duroplastic