

# Product data sheet

SCHUKO® socket with surge voltage protection



## Reference number

A 521 KIUF WW

SCHUKO® socket 16 A / 250 V ~

**with surge voltage protection**  
**with child protection (shutter)**  
 Screw terminals for wires up to 2.5 mm<sup>2</sup>

Without claws: ref.-no. with additional "N", e.g.: ..521 N..

## Intended use

- Type 3 fine protection for protecting electrical and electronic devices against transient power surges according to EN 61643-11
- For use only in combination with Type 1 coarse protection and Type 2 medium protection
- For use in TN, TT and IT systems
- Stationary installation indoors
- Installation in flush box according to DIN 49073

## Product characteristics

- The device protects electrical and electronic devices against transient power surges.
- Failure of the protection function is indicated by an acoustic and visual signal.

Aufdruck "Nur für EDV", "ZSV", "SV" gegen Aufpreis (Art.-Nr.: ..1520.. EDV, ..1520.. ZSV, ..1520.. SV).

## Technical data

Surge voltage protection:	type 3 surge arrester
Rated voltage UN:	AC 230 V ~
Mains frequency:	50/60 Hz
Max. continuous voltage UC:	AC 255 V ~
Open-circuit voltage UOC:	4 kV
Protection level between L/N:	≤ 1.25 kV
Protection level between L/PE:	≤ 1.25 kV
Protection level between N/PE:	≤ 1.25 kV
Rated load current IL:	16 A
Ambient temperature:	-5 ... +40 °C

## Duroplastic (scratch-proof) glossy

**Colour:**  
white

**Material:**  
duroplastic