

# Product data sheet

## Awning control, AeroTec 04



### Reference number

AT 04 WW

### Awning control, AeroTec 04

The AeroTec timer may be used to operate sun protection systems **only**.  
The AeroTec timer is pre-programmed ex works with current date and time (CET) settings and operates sun protection systems on the basis of sunlight intensity and wind speed. The AeroTec timer can be operated manually at any time. The device runs on battery power, meaning it can even be programmed if the operating device has been removed, as the display does not disappear.

- Controller for awnings
- 15 languages (Display)
- Ex works pre-programmed
- Sensors can be connected
- Manual control always possible
- Additional switching time
- Adjustable inside position
- Cloth stretching function

Always use shielded control wire ... 0.8 mm Ø or J-ST-Y ... 0.6 mm Ø

### Technical data

Rated voltage:	AC 230/240 V ~, 50/60 Hz
Switching current:	5 A / 250 V AC $\cos \phi = 1$
Switching capacity:	max. 1 motor 1000 W
Battery type:	1 x CR 2032
Output:	2 relays, floating contacts (NO contacts)
Input:	Brightness sensor (ref.-no.: LA 90) Sunlight / wind sensor (ref.-no.: AR 04) Wind sensor (ref.-no.: VT 04) Rain sensor (ref.-no.: RW 95)
Connection:	screw terminals
Terminals for:	2.5 mm <sup>2</sup>

### Thermoplastic (breakproof) high-gloss

**Colour:**  
white

**Material:**  
thermoplastic