

Product data sheet

LED wall luminaire (warm dim) Plug & Light



Reference number

 PL F1 WD05 AL-L

LED wall luminaire (warm dim) Plug & Light

for power supply Plug & Light, ref.-no.: PL 08 U

Intended use

- Dimmable light attachment for indoor lighting
- Mounting by plugging onto the light socket of the Plug & Light system

Product characteristics

- Accent lighting or work light
- Changing the colour temperature between 2700 K and 4000 K with simultaneous brightness increase from minimum to maximum, with suitable LED dimmer
- Non-glare asymmetrical optics
- Flicker-free light over the entire dimming range
- Light attachment can be changed during ongoing operation
- Stepless rotation through 360°

Technical data

Rated voltage:	DC 12 V SELV
Power consumption:	4.1 W
Connection:	electrical coupling via gold-plated sliding contacts
Protection class:	III
Dimensions (W x H x D):	70 x 70 x 17 mm
Luminous flux:	290 lm
Colour temperature:	2,700 ... 4,000 K
Colour rendering index:	typical 90
Beam angle:	asymmetrical light distribution
Energy efficiency class:	A++ to A

This luminaire contains built-in LED lamps.
The lamps can not be replaced in the luminaire.

metal versions

Colour:
aluminium (lacquered)

Material:
thermoplastic lacquered
