

Schede tecniche di Prodotto

Centralina di comando per tende avvolgibili "AeroTec 04"



Numero di riferimento

AT 04 WW

Awning control, AeroTec 04

The AeroTec timer may be used to operate sun protection systems **only**.
 The AeroTec timer is pre-programmed ex works with current date and time (CET) settings and operates sun protection systems on the basis of sunlight intensity and wind speed.
 The AeroTec timer can be operated manually at any time. The device runs on battery power, meaning it can even be programmed if the operating device has been removed, as the display does not disappear.

- Controller for awnings
- 15 languages (Display)
- Ex works pre-programmed
- Sensors can be connected
- Manual control always possible
- Additional switching time
- Adjustable inside position
- Cloth stretching function

Always use shielded control wire ... 0.8 mm Ø or J-ST-Y ... 0.6 mm Ø

Dati tecnici

Tensione nominale:	AC 230/240 V ~, 50/60 Hz
Corrente di commutazione:	5 A / 250 V AC cos φ = 1
Switching capacity:	max. 1 motor 1000 W
Tipo di batteria:	1 x CR 2032
Uscita	2 relays, floating contacts (NO contacts)
Input:	Brightness sensor (ref.-no.: LA 90) Sunlight / wind sensor (ref.-no.: AR 04) Wind sensor (ref.-no.: VT 04) Rain sensor (ref.-no.: RW 95)
Collegamento:	morsetti a vite
Terminals for:	2.5 mm ²

Termoplastic (infrangibile) extralucido

Colore:
 bianco alpino

Materiale:
 termoplastic